


Driver: _____
 Event: _____
 Date: _____
 Track: _____
 Surface: _____
 Temperature: _____

Vehicle: _____
 Firmware Version: _____
 Motor: _____
 Endbell Timing: _____
 Rotor: _____
 Final Ratio: _____



Data Record	Max. ESC Temperature: _____	Notes: _____ _____ _____ _____
	Max. Motor Temperature: _____	
	Min. Battery Voltage: _____	
	Max. Motor RPM: _____	

Type	Item	Value								
General Setting	Running Mode	Fwd/Brk	Fwd/Rev/B		Fwd/Rev					
	Reverse Force	25%	50%	75%	100%					
	Cutoff Voltage	Disabled	Auto	___ (3.0-11.1 Adjustable)						
	ESC Thermal Protection	105°C/221	125°C/257		Disabled					
	Motor Thermal Protection	105°C/221	125°C/257		Disabled					
	BEC Voltage	6.0V	7.4V							
	Remote Off	Enabled	Disabled							
	Sensor Mode	Full Sensored	Sensored/Sensorless Hybrid							
Throttle Control	Throttle Rate Control	___ (1-30 Adjustable)								
	Throttle Curve	Linear	Customize							
	Neutral Range	4%	6%	8%						
	Coast	___ (0%-20% Adjustable)								
	Drive Frequency	1K	2K	4K	8K	12K	16K			
	Softening Value	___ (0-25° Adjustable)								
	Softening Range	0%	10%	20%	25%	30%	35%	40%	45%	50%
Brake Control	Drag Brake	___ (0%-100% Adjustable)								
	Brake Force	0%	12.5%	25%	37.5%	50%	62.5%	75%	87.5%	100%
	Initial Brake Force	=Drag brake	___ (0%-50% Adjustable)							
	Brake Rate Control	___ (1-20 Adjustable)								
	Brake Curve	Linear	Customize							
	Brake Frequency	0.5K	1K	2K	4K					
	Brake Control	Linear	Traditional		Hybrid					
Timing	Boost Timing	___ (0-64° Adjustable)								
	Timing Activation	RPM	Auto							
	Boost Start RPM	___ (500-35000RPM Adjustable)								
	Boost End RPM	___ (3000-60000RPM Adjustable)								
	Turbo Timing	___ (0-64° Adjustable)								
	Turbo Delay	Instant	___ (0.05-1.0S Adjustable)							
	Turbo Increase Rate (deg/0.1sec)	6	12	18	24	30	Instant			
	Turbo Decrease Rate (deg/0.1sec)	6	12	18	24	30	Instant			