

RACE	Basic Clay Setup	
TRACK	Temperature: 20 degrees celsius	
NAME	TyTessmann	DATE 18/01/2019
LAPS	BEST LAP TIME	sec
QUALIFYING POSITION	FINAL POSITION	
TRACK SIZE	<input type="checkbox"/> OPEN	<input type="checkbox"/> MEDIUM <input type="checkbox"/> TIGHT
TRACK TRACTION	<input type="checkbox"/> HIGH	<input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> LOW
TRACK SURFACE	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM <input type="checkbox"/> BUMPY
TRACK TYPE	<input type="checkbox"/> HARD PACKED <input type="checkbox"/> SOFT DIRT	<input checked="" type="checkbox"/> CLAY
	<input type="checkbox"/> CARPET <input type="checkbox"/> BLUE GROOVE <input type="checkbox"/> ASTRO TURF	<input type="checkbox"/> GRASS
TRACK CONDITION	<input type="checkbox"/> DRY <input type="checkbox"/> DUSTY <input type="checkbox"/> WET	<input type="checkbox"/> MUD

DIFFERENTIAL TYPE		
FRONT ↓	MIDDLE ↓	REAR ↓
GEAR DIFF <input checked="" type="checkbox"/>	GEAR DIFF <input type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>
BALL DIFF <input type="checkbox"/>	SLIPPER <input checked="" type="checkbox"/>	BALL DIFF <input type="checkbox"/>
OIL 6K cst	OIL cst	OIL 4K cst
SATELLITE GEARS		
COMPOSITE <input type="checkbox"/>	COMPOSITE <input type="checkbox"/>	COMPOSITE <input type="checkbox"/>
STEEL <input checked="" type="checkbox"/>	STEEL <input type="checkbox"/>	STEEL <input checked="" type="checkbox"/>
CROWN GEAR		
COMPOSITE <input type="checkbox"/>	SLIPPER <input type="checkbox"/>	COMPOSITE <input type="checkbox"/>
STEEL <input checked="" type="checkbox"/>	mm	STEEL <input checked="" type="checkbox"/>
ALU <input type="checkbox"/>	SLIPPER ADJUSTMENT	ALU <input type="checkbox"/>

COMPOSITE <input type="checkbox"/>	PINION <input type="checkbox"/>	COMPOSITE <input type="checkbox"/>
STEEL <input checked="" type="checkbox"/>	STEEL <input checked="" type="checkbox"/>	STEEL <input type="checkbox"/>

GEARING	
PINION	SPUR GEAR

FRONT	SHOCKS	REAR
3 DOT	SPRINGS	2 DOT
cst 550	OIL	cst 500
% 0	REBOUND	% 0
<input checked="" type="checkbox"/> 2 HOLES	PISTONS	<input checked="" type="checkbox"/> 2 HOLES
<input type="checkbox"/> 3 HOLES	<input type="checkbox"/> ø1.2mm	<input type="checkbox"/> 3 HOLES
<input type="checkbox"/> 6 HOLES	<input type="checkbox"/> ø1.3mm	<input type="checkbox"/> 6 HOLES
HOLES	<input checked="" type="checkbox"/> ø1.4mm	HOLES
	<input type="checkbox"/> ø1.6mm	
	<input checked="" type="checkbox"/> ø1.7mm	
	CUSTOM PISTONS	
	a mm a mm	

FRONT	ANTI ROLL BAR	REAR
1.0 mm	THICKNESS	1.2 mm

FRONT	TIRES	REAR
	BRAND	
	COMPOUND	
	INSERTS	
	WHEELS	

ELECTRONICS		
MOTOR	6.0	XR10 PRO SPEEDO
MOTOR TIMING		4100 LCG BATTERY

ELECTRONICS LAYOUT		
MOTOR POSITION	FRONT <input checked="" type="checkbox"/>	REAR <input type="checkbox"/>
BATTERY POSITION	FRONT <input checked="" type="checkbox"/>	REAR <input type="checkbox"/>
BATTERY SIZE	STD. SHORT <input type="checkbox"/>	LOW SHORT <input checked="" type="checkbox"/>

COMMENTS
Front axle height middle.

